

Description

Halogen-free flame retardant scaffold sheeting made of 100% PE with strong eyelets

Fabric

Type	HDPE leno fabric, LDPE coating
Fabric weight	150 g/m ²
Tarp weight	160-170 g/m ²
Tensile strength	345 N/5 cm
Temperature resistance	-40 / +80 C°
Flame retardant	According to EN 13501-1 class B
UV stability	100 Kly
Light transmission	81%

Execution

Size	Finished size, +/- 2%
Joints	No joints
Finishing	With eyelet bands in length direction
Eyelet Bands	160 g/m ² with 15 mm Ø prepunched eyelets every 10 cm
Tear resistance eyelets	410 N/5 cm
Number of eyelet bands	4x for 2,70 m; 3,20 m
Number of eyelet bands	5x for 4,10 m

Size	Colours	Packing	Pallet
2,70 x 20 m	Natural	2 pcs / box	36 pcs
2,70 x 40 m	Natural	1 pc / roll	27 pcs
3,20 x 20 m	Natural	2 pcs / box	30 pcs
3,20 x 40 m	Natural	1 pc / roll	27 pcs
4,10 x 40 m	Natural	1 pc / roll	23 pcs

All data are average values only to be used for reference

Product and packing

Product Sheet

